

TUFLEX						
Tuflex is constructed of polyester coated in fire retardant anti-static pvc. It is recommended where service conditions require lightweight ducting and anti static environments.		NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	NOM WALL	Coil Length (m)
Colour / Black Temperature Range / -30 °C to 70 °C Material / Fras PVC		51	2	102	0.5	10
		57	2 ^{1/4}	114	0.5	10
		63	2 ^{1/2}	126	0.5	10
		76	3	152	0.5	10
		83	3 ^{1/4}	166	0.5	10
		89	3 ^{1/2}	178	0.5	10
		102	4	204	0.5	10
		114	4 ^{1/2}	228	0.5	10
		127	5	254	0.5	10
		152	6	304	0.5	10
		178	7	356	0.5	10
		203	8	406	0.5	10
		229	9	458	0.5	10
		254	10	508	0.5	10
		280	11	560	0.5	10
		305	12	610	0.5	10
		356	14	712	0.5	5
		381	15	762	0.5	5
		406	16	812	0.5	5
		457	18	914	0.5	5
	508	20	1016	0.5	5	
	559	22	1118	0.5	5	
	600			1220	0.5	5

Sizes from 356ml to 600mm manufactured to order.

T.P.R.D (THERMO PLASTIC RUBBER DUCTING)						
TPRD is constructed from a Thermo Plastic Rubber compound with a wire helix reinforcement. An excellent general purpose ducting with good abrasive qualities and UV resistance.		NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	NOM WALL	Coil Length (m)
Colour / Black Temperature Range / -50 °C to 100 °C Material / UV Resistant Rubber		39	1 ^{1/2}	80	0.6	10
		51	2	102	0.6	10
		63	2 ^{1/2}	126	0.6	10
		76	3	152	0.6	10
		89	3 ^{1/2}	178	0.6	10
		102	4	204	0.6	10
		114	4 ^{1/2}	228	0.6	10
		127	5	254	0.6	10
		152	6	304	0.6	10
		178	7	356	0.6	10
		203	8	406	0.6	10
		229	9	458	0.6	10
		254	10	508	0.6	10
		305	12	610	0.6	10
		356	14	712	0.6	5
		381	15	702	0.6	5
		406	16	812	0.6	5
		457	18	914	0.6	5
		508	20	1016	0.6	5
		559	22	1118	0.6	5
	600			1220	0.6	5

Sizes from 356ml to 600mm manufactured to order.

