

TUFF-RED DUCTING						
Tuff-Red is manufactured with a heavy duty wire for light suction applications and an anti-static, dry food grade polyurethane (PU). It is highly abrasive resistant with a smooth internal surface suitable for the conveyance of a wide range of materials.		NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	NOM WALL	Coil Length (m)
<b>Colour /</b> Translucent with Red wire <b>Temperature Range /</b> -30 °C to 100 °C <b>Material /</b> Polyurethane		51	2	102	1.0	10
		57	2 <sup>1/4</sup>	126	1.0	10
		63	2 <sup>1/2</sup>	152	1.0	10
		76	3	178	1.0	10
		89	3 <sup>1/2</sup>	204	1.0	10
		102	4	228	1.0	10
		114	4 <sup>1/2</sup>	254	1.0	10
		127	5	304	1.0	10
		152	6	356	1.0	10
		178	7	406	1.0	10
		203	8	458	1.0	10
		229	9	508	1.0	5
		254	10	560	1.0	5
		305	12	610	1.0	5
		356	14	712	1.0	5
		406	16	812	1.0	5
		457	18	914	1.0	5
		508	20	1016	1.0	5
		556	22	1118	1.0	5
		600		1220	1.0	5

HIGH TEMP. W						
High Temp W is manufactured utilising PTFE Coated materials creating a non stick high temp duct suitable for a wide range of applications.		NOM I.D (mm)	NOM I.D (inches)	Min.Bend Radius (mm)	NOM WALL	Coil Length (m)
<b>Colour /</b> Beige <b>Temperature Range /</b> -150 °C to 250 °C <b>Material /</b> PTFE Coated Glass Cloth		51	2	102	0.3	10
		76	3	152	0.3	10
		102	4	204	0.3	10
		127	5	254	0.3	10
		152	6	304	0.3	10
		178	7	356	0.3	10
		203	8	406	0.3	10
		229	9	458	0.3	10
		254	10	508	0.3	10
		305	12	610	0.3	5
		356	14	712	0.3	5
		381	15	762	0.3	5
		406	16	812	0.3	5
		457	18	914	0.3	5
		508	20	1016	0.3	5
		559	22	1118	0.3	5
		600		1220	0.3	5

