## The Future of

## **Hose Technology**

Barfell Nominal Product in mm's Code I.D. O.D.

Vacuum Rating KPa/20°C Working Pres. @ 20°C Mpa P.S.I.

Weight Kg/m

Min Bend Radius in mm Coil Lengths in Metres



Heavy duty flexible food quality PVC suction/discharge hose reinforced with a rigid spiral. Has a smooth bore to minimise flow losses.

206500	25	34.0	-90.0	0.7	100	0.60	160	20
206510	32	41.0	-90.0	0.7	100	0.71	190	20
206520	38	48.0	-90.0	0.6	85	0.82	230	20
206530	50	62.0	-90.0	0.5	75	1.20	290	20
206540	63	76.0	-90.0	0.5	75	1.73	360	20
206550	76	90.0	-90.0	0.5	75	2.29	450	20
206560	102	117.0	-90.0	0.4	60	3.33	640	20
206570	127	143.0	-90.0	0.4	60	4.58	900	Made to order
206580	150	170.0	-90.0	0.35	50	6.75	1,200	Made to order

**WINE** FOOD & BEVERAGE



Applications Suitable for the wine, canning and food packaging industries. It can be used for the suction of wine & spirits up to 28 1/4 proof. The smooth bore enables easy cleaning and reduces bacteria buildup.

Colour Clear with Claret Spiral
Temperature Range -5°C to +60°C

Chemical Resistance Flexibility Excellent Good Abrasion Resistance Conforms to Excellent AS2070

An exceptionally flexible, clear suction/discharge hose suitable for food and beverages. The clear rigid helix makes the hose completely transparent. It is UV light stabilised and conforms to AS2070 1999.

206482	25	32.0	-90.0	1.0	145	0.43	120	20
206484	32	40.6	-90.0	0.9	130	0.65	150	20
206486	38	45.6	-90.0	0.9	130	0.70	200	20
206488	50	60.2	-90.0	0.7	102	1.05	270	20
206490	63	73.5	-90.0	0.6	87	1.44	330	20
206492	75	87.8	-90.0	0.6	87	1.98	440	20
206494	100	116.6	-90.0	0.5	73	3.14	620	20

**C VIEW S** 



Applications Suction of any fluid that requires a food grade hose including wineries, milk collection or processing, canneries, and food processing plants. It can be used for the suction or delivery of wine & spirits to 28 1/4 proof.

Colour Clear with Clear Rigid PVC Spiral Temperature Range -5°C to +60°C

Chemical Resistance Flexibility Excellent Excellent

Abrasion Resistance Conforms to Good AS2070

Specifically designed to outperform all other hoses in the beverage industry. It is both a suction and pressure hose in one. It is UV light stabilised, conforms to AS2070 for use with food products and uses a plastic helix that will not rust or cut the hands of operators.

206000	25	35.4	-90.0	1.2	175	0.68	130	30
206005	38	49.9	-90.0	1.2	175	1.01	220	30
206010	50	64.4	-90.0	1.0	145	1.67	300	30
206012	76	92.4	-90.0	1.0	145	2.57	490	20

**C VIEW SP** 



Applications Pressure or suction of any liquid or semi liquid that requires a food grade hose. Included are wineries, milk processing plants or tankers. Can be used with wine and spirits to 28 1/4 proof.

Colour Clear with Clear Rigid PVC Spiral Temperature Range -5°C to +60°C

Chemical Resistance Flexibility

Excellent Excellent Abrasion Resistance Conforms to

Excellent AS2070